

GENERATING SET GE 2000 SX

- Honda OHV gasoline engine
- Engine protection (oil)
- Single phase synchronous alternator
- Suitable for electronic equipment
- Recessed sockets
- Circuit breaker / GFI - ELCB
- Protective frame
- Complies with EEC directives



Standard equipment 										
	Gasoline engine	Air cooling	Manual recoil	Oil alert	Engine shut down (oil)					
	Synchronous alternator	Socket 230V Schuko	Thermal shut off	Ground fault interrupter	Battery charger					

Options on request

- Plug 230V 16A 2PT (M) SCHUKO
- Battery cables set
- Earthing Kit MT10

Technical Data

GE 2000 SX

A.C. GENERATION	50 Hz, synchronous, single-phase, self-excited, self-regulated, brushless
Single-phase generation	1.5 kVA / 230 V / 6.5 A
Battery charge d.c.	12V - 10A
Duty cycle	100%
Power factor (cos φ)	1
Insulation class	H
On request other voltages and frequencies (60 Hz)	

ENGINE	Gasoline, 4-stroke, air cooled
Type	HONDA GX 120 K1
Output*	2.6 kW (3.5 HP)
Speed	3000 rpm
Displacement	118 cm ³
Cylinders	1
Fuel consumption	313 g/kWh
* Maximum output according to ISO 3046/1	

GENERAL SPECIFICATIONS	
Tank capacity	2.5 l
Running time (Load 75%)	3.5 h
Protection	IP 23
Dimensions Lxwxh (mm)	480x370x400
Weight	35 kg
Noise level **	96 LWA (71 dB(A) - 7 m)
** LWA conforms to EEC Directive 536	

Values shown are nominal values. For further information please contact the sales department.